




---

 PRODUCT-DETAILS

## ACS880-01-430A-3

LV AC industrial wall-mounted single drive,  
IEC: Pn 250 kW, 430 A, 400 V (ACS880-01-430A  
-3)




---

### General Information

Global Commercial Alias	ACS880-01-430A-3
Product ID	3AUA0000108038
ABB Type Designation	ACS880-01-430A-3
EAN	6438177555216
Catalog Description	LV AC industrial wall-mounted single drive, IEC: Pn 250 kW, 430 A, 400 V (ACS880-01-430A-3)

The ACS880-01 drives are customized to meet the particular needs of specific industries, such as oil and gas, mining, metals, chemicals, cement, power plants, material handling, pulp and paper, sawmills, marine, water and wastewater, food and beverage, and automotive. They can control a wide range of applications, including cranes, extruders, winches, winders, conveyors, mixers, compressors, centrifuges, test benches, elevators, extruders, pumps and fans.

#### Long Description

The ACS880-01 comes in one compact package for easy installation and commissioning. The drive can be installed on the wall as standard and in a cabinet as an option. The drive offering includes enclosure classes up to IP55, making it suitable for most environments and installations. ACS880-01 drives have all the essential features built-in. These features include as standard a choke for harmonic filtering as well as options like a brake chopper, EMC filter and communication protocol adapter, functional safety, external output filters and I/O extension modules.

---

## Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS880-01-430A-3 PN: 250 kW, IN: 430 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	209.439 lb
Product Net Depth / Length	16.260 in
Product Net Height	37.598 in
Product Net Width	14.961 in
Package Level 1 Depth / Length	45.08 in
Package Level 1 Height	25.75 in
Package Level 1 Width	19.09 in
Package Level 1 Units	1 case

## Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m
	5 ... 95
Sound dB (A)	70 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 2 pcs, 6 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R9
Input Voltage (U <sub>in</sub> )	380 ... 415 V
Mounting Type	Wall-mounted
Communication Protocol	PROFINET IO
Number of Hardware Interfaces	Industrial Ethernet 0 Other 4 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 2
Output Current, Normal	430 A

Use ( $I_n$ )	
Output Current, Light-	400 A
Overload Use ( $I_{LD}$ )	
Output Current, Heavy-	363 A
Duty Use ( $I_{HD}$ )	
Output Power, Normal	250 kW
Use ( $P_n$ )	
Output Power, Light-	200 kW
Overload Use ( $P_{LD}$ )	
Output Power, Heavy-	200 kW
Duty Use ( $P_{HD}$ )	
Apparent Power Output	298 kV·A
Efficiency Level	IE2
Standby Loss	83 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	1409 W	91.9 %	0.5 %
0/50 %	2137 W	93.6 %	0.7 %
0/100 %	3880 W	94.1 %	1.3 %
50/25 %	1500 W	95.7 %	0.5 %
50/50 %	2265 W	96.6 %	0.8 %
50/100 %	4452 W	96.7 %	1.5 %
90/50 %	2662 W	97.8 %	0.9 %
90/100 %	5797 W	97.6 %	1.9 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

### External Classifications and Standards

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

### Environmental

SCIP	ba3bb48e-e4aa-436e-b075-d205051c83ef Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

### Additional Information

Product Name	Frequency converter
--------------	---------------------

---

## Categories

---

Drives → Low Voltage AC Drives → Industrial Drives → ACS880 Single Drives → ACS880-01 - Wall-mounted single drive

